

RAPID8

8W 3CCT DOWNLIGHT + RAPID CONNECTOR



RAPID INSTALL



TOOL-LESS



ONLY SUITABLE FOR
1.5MM² CABLE*



DIMMABLE



90 MINUTE
FIRE RATED



UNIVERSAL POLARITY








600mm



MLI-RAPID8UK-MULTI

Total power consumed:	8W
Lumen output:	655lm (WW) 736lm (NW) 648lm (W)
Colour temperature:	3,000K (WW) 4,000K (NW) 6,000K (W)
CRI:	>80
Efficacy:	>81-92lm/W
Beam angle:	60 degrees
Dimmable:	Yes (see website)
Power supply:	220-240V AC integral driver
Average life:	40,000hrs**
Operating temperature	-10°C to 45°C
Installation temperature	15°C to 45°C
Connection:	600mm flex & RAPID connector
Bezel:	White (interchangeable)
Mounting method:	Ceiling recessed
Gimbal angle:	Fixed
Cut out:	70mm
Downlight dimensions:	H 79mm W 65mm Trim Diameter 85mm
Connector dimensions:	H 30mm W 53mm L 73mm
Material type:	Chassis: Mild steel Lens: PMMA Bezel: Polycarbonate Heatsink: Aluminium Finish: Powder coat Connector: Polycarbonate
Suits cable:	1.5mm ² Twin core + Earth 6242YH, BS6004
*Compatible cables:	Prismian UK cable 2016 1.5mm 2C + E PX cables 179/001 (dark grey) 1.5mm 2C + E PX cables 187/001 (light grey) 1.5mm 2C + E Doncaster Electric cable H6242Y 2x1.5+1.0
Fire rating:	90 minutes
IP rating:	IP65 (downlight face only)
Optional trims:	Brushed nickel bezel, chrome bezel
Kit includes:	1x Downlight + RAPID connector, 1x instructions & FAQ, 1x terminator
Compliance:	BS EN60598-1:2015, BS EN60598-2-2:2012, EMC: EN55015, EN61547, EN62493, EN61000-3-2, EN61000-3-3, IEC60998-2-3, IEC60998-1, BS5733, BS476-20



**Average life is calculated on expected average lifespan
Due to our policy of continuous product improvement, we reserve the right to discontinue or update product specifications or designs at any time without notice. Please visit www.m-elec.com for the latest information on our products.